

High Speed Colour Duplex Scanner

fi-4860C2 Image Scanner



148 images per minute scanning speed
@200 dpi, colour or monochrome

Auto colour detection, blank page deletion,
auto cropping, and auto de-skew

500 page automatic document feeder

Ultrasonic multi-feed detection

Kofax VRS® 4 Production hardware
processing delivers excellent image quality

1 year on-site warranty



Adobe Acrobat
7.0 Standard

FUJITSU

THE POSSIBILITIES ARE INFINITE

fi-4860C2

Image Scanner



VRS® 4 Professional Production Included

VRS 4 Professional Production is included with every fi-4860C2. VRS provides many advanced Imaging functions that greatly increase overall efficiency in a Production scanning environment.

Fast VRS Scanning Speed

74 ppm/148 ipm @200 dpi, Letter, Landscape in B/W, Greyscale and Colour is achieved with VRS.

Excellent Paper Handling

13.9 to 34 lb paper is supported through the automatic feeder.



Ultra-sonic Multi-Feed Detection

Ultra-sonic multi-feed detection is the most advanced method for detecting multi-feeds. It works reliably even when scanning pages of different sizes, thicknesses and colours.

Auto Switching Background

Allows the software or scanner to switch between a white and black background. A black background is required for accurate auto-crop and auto deskew. A white background is required to perform optical system checks and re-calibrations which contribute to consistent image quality.

Imprinter Option

The imprinter option prints a string of alphanumeric text onto the back side of the page after scanning. This text can include a page counter, date and time, file number or any other alphanumeric information.

TECHNICAL SPECIFICATIONS

| | | |
|--|---|--|
| Scanner type | ADF (Automatic Document Feeder) / Manual feed | |
| Scanning modes | Simplex / Duplex; Colour / Greyscale / Monochrome | |
| Image sensor type | Dual colour CCDs (Charged Coupled Device) | |
| Light source | White fluorescent lamp | |
| Scanning range | <i>Minimum</i> | 2.9" x 2.9" |
| | <i>Maximum</i> | 11" x 17" |
| Paper weight (Thickness) | 13.9 to 34.0 lb. | |
| Scanning speed¹ (Letter, Landscape, 200 dpi) | 74 ppm / 148 ipm (colour ² , greyscale ² , or monochrome) | |
| Paper chute capacity | Max. 500 sheets (20 lb.) | |
| Background colours | Black and white (auto-switching) | |
| Optical resolution | 400 dpi | |
| Output resolution | <i>Colour</i> | 100 / 150 / 200 / 300 / 400 dpi |
| | <i>Greyscale</i> | 100 / 150 / 200 / 240 / 300 / 400 dpi |
| | <i>Monochrome</i> | 100 / 150 / 200 / 240 / 300 / 400 dpi |
| Output format | 24 bit (colour), 8 bit (greyscale), or 1 bit (monochrome). | |
| AD converter | 10 bit | |
| Interface | Ultra-wide SCSI | |
| Connector shape | Shield type 68-pin (pin type) | |
| SCSI terminator | Built-in | |
| Output mode | Dither / Error diffusion | |
| Voltage or voltage range | AC 100 to 120 V, +/-10%; 50/60 Hz +2% / -4% | |
| Power | <i>Operating</i> | 200 watts or less. |
| | <i>Sleep mode</i> | Less than 12 watts. |
| Operational environment | <i>Temperature</i> | 15°C to 35°C (59°F to 95°F) |
| | <i>Relative humidity</i> | 20% to 80% (non-condensing) |
| Dimensions (W x D x H) | 520 mm x 431 mm x 523 mm (20.5" x 17.0" x 20.6") | |
| Weight | 49 kg (99 lb.) | |
| Environmental compatibility | RoHS. | |
| Other | <i>Multi-feed detection</i> | Standard; Ultrasonic multi-feed detection sensor. |
| | <i>Paper counter</i> | Standard. |
| | <i>Image processing</i> | Auto crop, auto de-skew, auto colour detection, auto page orientation, blank page detection. |
| | <i>Dropout colour</i> | Selectable dropout colour (red, green, or blue). |

OPTIONS

| | |
|---|---|
| Pre-scanning imprinter (fi-485PRFR) PA03296-D207 | The imprinter option enables users to print information on original documents for document management purposes. |
| Post-scanning imprinter (fi-486PRRE) PA03296-D201 | While the fi-486PRFR prints information on the front of documents prior to scanning, the fi-486PRRE prints information of the back of the original documents after they have been scanned. Although both the fi-486PRFR and the fi-486PRRE may be attached to the same scanner unit, both imprinters cannot be used simultaneously. |

CONSUMABLES

| | |
|--------------------------------------|--|
| ScanAid kit CG01000-498501 | Up to 300,000 sheets or 1 year. The kit includes 1 pick roller, 1 brake roller, 1 pad assembly, and 1 cleaning kit. |
|--------------------------------------|--|

SERVICE OPTIONS

| | |
|---|--|
| Post warranty maintenance coverage | Provides post warranty remedial maintenance. |
|---|--|

BUNDLED ITEMS

| | |
|--|---|
| | AC power cable, Installation guide, Adobe® Acrobat® 7.0 Standard, ScandAll 21, ISIS/TWAIN drivers, Kofax VRS® 4 Production. |
|--|---|

WARRANTY

| | |
|--|---|
| | 1 year on site. Visit www.fujitsu.ca/warranty/scanner/ for more details. |
|--|---|

1) Actual scanning speeds are affected by data transmission and software processing times.
2) Using JPEG compression.

Fujitsu and the Fujitsu logo are registered trademarks of Fujitsu Limited. Adobe, Acrobat, Adobe PDF logo are either registered trademarks or trademarks of Adobe Systems Incorporated in the United States and/or other countries. Kofax, VirtualReScan, Adrenaline and the "VRS VirtualReScan" logo are registered trademarks of Kofax Image Products. All the other trademarks mentioned herein are the property of their respective owners. Specifications are subject to change without notice.
© 2006 Fujitsu Canada, Inc. All rights reserved. FCI-12.04.2006-E



MultiCIM Technologies Inc.
640 Bord du Lac/Lakeshore, suite 101
Montréal (Dorval), QC, CANADA H9S 2B6
T : (514) 633-6401 or 1 (877) MULTICIM
F : (514) 633-6495
sales@exadox.com



THE POSSIBILITIES ARE INFINITE