

THE POSSIBILITIES ARE INFINITE

FUJITSU

A4 COLOUR  
DUPLEX  
DOCUMENT  
SCANNER

# fi-5110C Image Scanner



Adobe **Bundled!**  
Acrobat® 6.0  
Standard

• Convert any document to a PDF file



• Fujitsu TWAIN driver




• Genuine Pixel Translation ISIS driver



As an EnergyStar® Partner, Fujitsu has determined that this product meets the EnergyStar guideline for energy efficiency. EnergyStar is a U.S. registered mark.

for Microsoft® Windows®  
Operating Systems

## QUALITY SCANNER



## TECHNICAL SPECIFICATIONS

The fi-5110C image scanner with USB 2.0 interface capability expands the market for production scanning.

- **Small Footprint**
  - (W) 293.5 x (H) 130.0 x (D) 166.0mm
- **Fast scanning speed in its class**
  - 15 ppm/30 ipm Letter portrait at 150 dpi (colour)
  - 15 ppm/30 ipm Letter portrait at 200 dpi (monochrome)
- **Superior paper handling**
  - 50 Sheet ADF Capacity
  - IR multi feed detection
  - Straight paper path and easy maintenance
- **Excellent image quality**
  - Optical Resolution of 600 dpi
  - Image processing software V2.0 (Option)
  - Superior CCD (charge-coupled device) image sensing technology
  - Supports sRGB technology
- **Superior input/output performance**
  - USB 2.0 interface
- **Easy to use**
  - Bundled with ScandAll21, Adobe Acrobat 6.0 Standard and other software



Scanner Type		ADF (Automatic Document Feeder)
Image Sensor Type		Colour CCD (Charge-Coupled Device) x 2
Light Source		White cold cathode discharge lamp
Optical Resolution		600 dpi
Output Resolution	Colour	50 to 600 dpi
	Greyscale	50 to 600 dpi
	Monochrome	50 to 600 dpi
Internal Video Processing		1024 levels (10-bit)
Output	Colour	8 and 24-bit / pixel
	Greyscale	8-bit / pixel
	Monochrome	1-bit / pixel
Scanning Speed (Letter, portrait)	Colour (150 dpi)	15 ppm(Simplex) / 30 ipm(Duplex)
	Monochrome (200 dpi)	15 ppm(Simplex) / 30 ipm (Duplex)
Document Size	Minimum	2.1" x 2.9"
	Maximum	8.5" x 14"
Document Weight		52 to 127 g/m <sup>2</sup> , or 14 to 34 lb
Capacity		Maximum 50 sheets, 80 g/m <sup>2</sup> or 20 lb
Background		White
Interface		USB 2.0 x 1 *Also works with USB 1.1
Connector Shape		USB (B type)
Image Processing		Image emphasis, simplified DTC, error diffusion, dither, moire removal Non-dropout colour (Generated by the driver)
Voltage or Voltage Range		AC 100 to 240 V, +10% / -10%
Power	Operating	28 W
	Sleep mode	Less than 6 W
	Turned off while plugged in	1 W
Operational Environment	Temperature	5 to 35 °C (42 to 95 °F)
	Relative humidity	20 to 80% (non-condensing)
Dimensions	Width	293.5 mm (11.6")
	Depth	166.0 mm (6.5")
	Height	130.0 mm (5.1")
Weight		2.7 kg
Option		Image processing software option V2.0
Others Functions	Multi feed detection	Yes, IR multi feed detection sensor
	Long paper scanning	864 mm (34")
	Paper counter	Yes
Consumables	Pick Roller (PA03360-0001)	Lifetime: Every 100,000 sheets or one year
	Pad ASSY (PA03360-0002)	Lifetime: Every 50,000 sheets or one year

Microsoft, Windows and Windows NT are registered trademarks of Microsoft Corporation in the United States and/or other countries. ISIS, QuickScan and their respective logos are trademarks or registered trademarks of Pixel Translations, a division of Captiva Software Corporation. Adobe, Adobe logo and Acrobat are either registered trademarks of Adobe Systems Incorporated in the United States and/or other countries. Other product names are the trademarks or registered trademarks of the respective companies. Specifications are subject to change without notice. For the latest information, contact your local Fujitsu representative. First edition September 2004

**FUJITSU CANADA, INC.**  
 6975 Creditview Road, Unit 1, Mississauga, Ontario L5N 8E9  
 Telephone: (905) 286-9666 Fax: (905) 286-5998 Toll Free: 1-800-263-8716  
<http://www.fujitsu.ca>

**QUEBEC / ATLANTIC PROVINCES**  
 1000 Sherbrooke Street West, Suite 1500, Montréal, Québec H3A 3G4  
 Telephone: (514) 288-6262 Fax: (514) 288-0756 Toll Free: 1-800-663-0756  
<http://www.fujitsu.ca/fr>